



Technical information

Power amplifier module compatible with FIGARO™

Power supply

V: Input 110—230V 3A Output 12V cc
MTBF: 25'000h
Protection IP: 20
Cooling: convezione
Working temp.: 0 C° > +90C°
Humidity (%): 5 - 95

Amplifier

Class: D - chip MAXIM MAX9736
V: 12V cc 3A
Max power: 30W
Crossover: integrato low pass @300Hz
Shutdown mode: automatic @1μA
Tension protection.: auto switch-off >@ 4,6A
Thermal protection: auto switch-off >@160°C

Dimensions and weight

Height: 52mm
Base dimensions: 130mm (diagonal)
Weight: 180g

Certifications

89/336/CE—EMC
73/23/CE—Low voltage
Made in Italy
CE

Applications

Plasterboard
Plywood
MDF
Plexiglass
Fiberglass, Carbon fiber
Metal
Glass
Corian by Du Pont
others

Control modules and optional

Ultra flat wire mod. F.Ribbon
Power amplifier mod. F.Amp/F.Fil
Passive crossover mod. F.Fil (optional)
Mid-Hi frequencies device mod. F.25

Warranty and assistance

Warranty: as forecasted by CE laws
Assistance: info@esarc.com

Contenuto della confezione

1 amplifier switching class D
1 power supply 110-230V 3A
1 bond tape
1 base
instructions

